

Summary of Test Results
in accord with FCC Rules Part 15 and C63.4-1992

Equipment Model: ACP00872

Transmitter Tested to C63.4-1992 Section: FCC Rules 15.231

Field Strength at a distance of 3 meters: 4841 uV/Mtr (-2.0 dB below limit) @ 318 MHz

Peak to Average Ratio: 15.6 dB - Fixed Duty Cycle

Test Conditions: Radiated (Sections 11 & 13)

Transmitter:
Transmitter Frequency: 318 MHz Nominal (Factory Tuned Only)

Bandwidth (20 dB down) < 0.010% of Center Freq.

Frequency Tolerance: N/A (Nominal +/- 0.125 MHz)

Frequency Stability: N/A (Nominal +/- 0.250 MHz)

Transmitter Spurious at 3 meters:
(Worst Harmonic) 467 uV/Mtr (-2.33 dB below limit)

Frequency: 636 MHz

Momentary Operation (Yes/No) Yes

Holdover time after manual release: 0.0 seconds


Duration of transmission after activation: 10 seconds maximum on any single manual activation

Attestation:


The radio apparatus identified in the application has been subject to all the applicable test conditions specified in FCC Rules Part 15 and all of the requirements of the Standard have been met.

Regulatory Compliance Engineer

John W. Kuivinen, P.E.



Date:



LINEAR CORPORATION
FCC ID: EF4 ACP00872
